

Cast Iron Jet Pump

Features

- Cast iron pump housing.
- Suitable for water supply and drainage in garden irrigation, greenhouses, fish breeding and poultry raising.
- Also can be used for domestic automatic water supply places, such as lifting water from a deep well, pressure boosting of running water etc.
- Motor with thermal protector.



Type Cast iron jet pump

Model	XKJ-600I	XKJ-800I	XKJ-900I	XKJ-1100I	XKJ-1300I
Supply Power	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
Input Power	600W	800W	900W	1100W	1300W
Max. Head	35m	40m	42m	45m	48m
Max. Flow	3.6m ³ /h	3.6m ³ /h	3.6m ³ /h	4.6m ³ /h	5.0m ³ /h
Max. Suction	8m	8m	8m	8m	8m
Max. Dis. of Particle	0.2mm	0.2mm	0.2mm	0.2mm	0.2mm
Outlet/Inlet	G1 × G1	G1 × G1	G1 × G1	G1 × G1	G1 × G1
Cable	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m
Operating Limits:	Fluid temperature up to 35°C; Ambient temperature up to 40°C				



Type Cast iron jet pump

Model	XKJ-601I	XKJ-801I	XKJ-901I	XKJ-1101I	XKJ-1301I
Supply Power	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
Input Power	600W	800W	900W	1100W	1300W
Max. Head	35m	40m	42m	45m	48m
Max. Flow	3.6m ³ /h	3.6m ³ /h	3.6m ³ /h	4.6m ³ /h	5.0m ³ /h
Max. Suction	8m	8m	8m	8m	8m
Max. Dis. of Particle	0.2mm	0.2mm	0.2mm	0.2mm	0.2mm
Outlet/Inlet	G1 × G1	G1 × G1	G1 × G1	G1 × G1	G1 × G1
Cable	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m
Operating Limits:	Fluid temperature up to 35°C; Ambient temperature up to 40°C				