

## VENTILOCONVECTOARE CASETA WARMMAN

model (2 tevi)				MFP-34KM	MFP-51KM	MFP-68KM	MFP-85KM	MFP-102KM	MFP-136KM	MFP-170KM	MFP-204KM	MFP-238KM	
Volum aer	treapta 3		m <sup>3</sup> /h	340	510	680	850	1020	1360	1700	2040	2380	
	treapta 2			280	380	515	660	765	1040	1280	1550	1800	
	treapta 1			180	260	340	430	530	710	860	1050	1280	
Putere Racire	TH	treapta 3	W	<b>1800</b>	<b>2700</b>	<b>3600</b>	<b>4500</b>	<b>5400</b>	<b>7200</b>	<b>9000</b>	<b>10800</b>	<b>12600</b>	
			BTU/h	6142	9212	12283	15354	18425	24566	30708	36850	42991	
			SH	W	1311	1971	2700	3184	4196	5362	6707	8072	9070
	SH	treapta 2	BTU/h	4473	6725	9212	10864	14317	18295	22884	27542	30947	
			W	1500	2460	3000	3715	4423	6435	7848	9296	10500	
			W	994	1555	1995	2426	3041	4236	5393	6603	7190	
TH	treapta 1	W	1391	2057	2479	2921	3793	5604	7223	8534	8900		
		W	823	1200	1530	1826	2373	3284	4416	5248	5500		
Putere Incalzire	treapta 3		W	<b>2700</b>	<b>4050</b>	<b>5400</b>	<b>6750</b>	<b>8100</b>	<b>10800</b>	<b>13500</b>	<b>16200</b>	<b>18900</b>	
	treapta 2		W	1949	2770	3938	4902	5694	7924	10473	12997	13900	
	treapta 1		W	1297	1774	2779	3505	3876	5421	6992	8645	9700	
Nivel Zgomot	H	0Pa	dB(A)	37	39	41	43	45	46	48	50	51	
Putere motor	H	0Pa	W	37	52	62	76	96	134	152	189	228	
Debit apa			m <sup>3</sup> /h	0,31	0,46	0,62	0,77	0,93	1,23	1,54	1,85	2,16	
Pierdere presiune			kPa	11,8	11,8	22,4	27	29,6	29,6	35,4	35,4	40	
Racorduri hidraulice			in	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	
			out	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Racord evacuare condens			mm	∅ 26	∅ 26	∅ 26	∅ 26	∅ 26	∅ 26	∅ 26	∅ 26	∅ 26	
Dimensiuni	VTCV	LxWxH	590*590*270				752*752*293			822*822*263		822*822*293	
	panou		650*650*45				850*850*45			950*950*45			
Greutate	VTCV	kg	19	19	20	23	23	25	28	28	29		
	panou		2,2			4,5			6				
Alimentare electrica				1x220V, 50Hz									