



Yalıtımdaki Gelecek

**PRODUCT DATA SHEET**

Document: PDS-ALU FD

Rev.No:00

Issue date: 01.07.2007

Page:1/1

**PRODUCT NAME: ODE DUCTFLEX ALU FD****Description**

No insulated flexible airtight ducts consist of a bronze covered spiral steel wire inserted into the several aluminium foil and polyester film laminated layers, for various purposes without special demands.

**Product features**

Standard	TS EN 13180															
Dimensions	Diameter range (mm)	Ø102-Ø127-Ø152-Ø165-Ø185-Ø203-Ø229-Ø254-Ø305-Ø315-Ø356-Ø406-Ø457-Ø508														
	Length	10 m ± 3%														
	Wall thickness	0,065-0,085 mm														
	Wire spacing	36 mm (18 mm**) ** In case of special demand ALU FD series ducts could be produced double wired.														
Material structure	3 layers Aluminium foil															
	2 layers Polyester film															
	Wire															
	Adhesive															
Service Temperature:	-30 / + 140 °C															
Max. Air Velocity:	30 m/s															
Max. Operating Pressure:	2500 Pa															

**Packing:**

Single duct in cardboard box.

Diameter (mm)	102	127	152	165	185	203	229	254	305	315	356	406	457	508
Box / Palette	360	224	168	168	90	90	56	56	36	36	15	10	8	8

**Storage:**

ODE DUCTFLEX flexible ducts should be stored in dry plase and away from heat sources.