

VENTILOCONVECTOARE DE PARDOSEALA - MFP-TM

MODEL (2 tevi)			MFP-34LM	MFP-51LM	MFP-68LM	MFP-85LM	MFP-102LM	MFP-136LM	MFP-170LM	MFP-204LM	MFP-238LM	
Tensiune alimentare			220V,50Hz,1Ph									
Debit aer	treapta 3	m ³ /h	340	510	680	850	1020	1360	1700	2040	2380	
	treapta 2		260	390	510	640	770	1020	1280	1530	1790	
	treapta 1		170	260	340	430	510	680	850	1020	1190	
Presiune statica			Pa	12(30)	12(30)	12(30)	12(30)	12(30)	12(30)	12(30)	12(30)	
Capacitate Racire	TH	treapta 3	W	1800	2700	3600	4500	5400	7200	9000	10800	12600
			BTU/h	6142	9212	12283	15354	18425	24566	30708	36850	42991
	SH	treapta 3	W	1368	2052	2736	3420	4103	5471	6839	8207	9575
			BTU/h	4668	7001	9335	11669	13999	18667	23335	28002	32670
	TH	treapta 2	W	1494	2242	2989	3736	4483	5978	7472	8967	10461
			W	1181	1771	2362	2952	3541	4722	5903	7084	8265
	SH	treapta 1	W	1162	1744	2325	2906	3487	4649	5812	6974	8136
			W	953	1430	1907	2383	2860	3813	4765	5718	6672
Capacitate Incalzire	treapta 3		W	2700	4050	5400	6750	8100	10800	13500	16200	18900
	treapta 2		W	2131	3197	4262	5328	6393	8524	10655	12786	14917
	treapta 1		W	1675	2511	3349	4186	5024	6697	8372	10046	11721
Nivel zgomot	treapta 3	12Pa	dB(A)	35	36	38	40	43	44	45	46	49
		30Pa		39	41	43	45	48	49	50	52	54
Putere motor	treapta 3	12Pa	W	34	41	59	73	91	118	146	182	216
		30Pa		41	54	65	82	98	132	168	206	247
Debit agent termic			m ³ /h	0,31	0,46	0,62	0,77	0,93	1,23	1,54	1,85	2,16
Pierdere presiune agent termic			kPa	7	15	18	23	28	30	22	30	36
Racord agent termic				ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"
				ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"	ZG3/4"
Racord evacuare condens			mm	ZG3/4"								
Dimensiuni	L×W×H		mm	858*235*608	908*235*608	1058*235*608	1208*235*608	1258*235*608	1608*235*608	1758*235*608	1908*235*608	2058*235*608
Greutate			kg	22	24	25	29	32	46	50	56	60