



Boilere electrice uz casnic

**GCA 1015 SRC**

**GCA 1515 SRC**

**GCU 1015 SRC**

**GCU 1515 SRC**

Boilere electrice - montare deasupra chiuvetei (GCA) si sub chiuveta (GCU)



GCU



GCA



On/Off switch

Buton ON/OFF



Above the sink  
installation

Instalare  
deasupra  
chiuvetei  
(GCA)



Adjustable room  
thermostat

Termostat  
reglabil



Under the sink  
installation

Instalare  
sub  
chiuveta  
(GCU)



| Informatii principale                                                                              |
|----------------------------------------------------------------------------------------------------|
| <p>Panou de comanda usor de utilizat</p> <p>Montare usoara deasupra sau sub chiuveta / lavoar.</p> |



| Caracteristici tehnice GCA 1015 SRC                            |  |                         |
|----------------------------------------------------------------|--|-------------------------|
| Nominal capacity [L] - Capacitate nominala [L]                 |  | 10 L                    |
| Protection of the tank - Protectie rezervor                    |  | sticla ceramica         |
| Rated voltage [V/Hz]] - Tensiune de alimentare [V/Hz]          |  | 230V/50Hz               |
| Rated power [W]] - Putere boiler electric [W]                  |  | 1500 W                  |
| Rated pressure of the water tank - Presiune de lucru [MPa]     |  | 0.8 MPa                 |
| Insulation [mm] - Izolatie [mm]                                |  | 19 mm                   |
| Heating time from 15°C to 65°C - Incalzire de la 15 la 65 grdC |  | 23 min                  |
| Switch On / Off - Buton ON / OFF                               |  | Yes                     |
| Adjustable thermostat - Termostat reglabil                     |  | Yes                     |
| Magnesium anode - Anod de magneziu                             |  | Yes                     |
| Anode tester - Tester anod                                     |  | No                      |
| Safety valve - Supapa de siguranta                             |  | Yes                     |
| Dimensions H / W / D [m] - Dimensiuni H / L / A [m]            |  | 0.410 x 0.370 x 0.250 m |
| Net weight [kg] - Greutate neta [kg]                           |  | 6.50 kg                 |
| Installation - Montare                                         |  | deasupra chiuvetei      |
| Warranty (full) - Garantie                                     |  | 2 years                 |



| Caracteristici tehnice GCA 1515 SRC |                         |
|-------------------------------------|-------------------------|
| Nominal capacity [L]                | 15 L                    |
| Protection of the tank              | Glass ceramic           |
| Rated voltage [V/Hz]                | 230V/50Hz               |
| Rated power [W]                     | 1500 W                  |
| Rated pressure of the water tank    | 0.8 MPa                 |
| Insulation [mm]                     | 19 mm                   |
| Heating time from 15°C to 65°C      | 35 min                  |
| Switch On / Off                     | Yes                     |
| Adjustable thermostat               | Yes                     |
| Magnesium anode                     | Yes                     |
| Anode tester                        | No                      |
| Safety valve                        | Yes                     |
| Dimensions H / W / D [m]            | 0.410 x 0.370 x 0.310 m |
| Net weight [kg]                     | 8.50 kg                 |
| Installation                        | deasupra chiuvetei      |
| Warranty (full)                     | 2 years                 |



| Caracteristici tehnice GCU 1015 SRC |                         |
|-------------------------------------|-------------------------|
| Nominal capacity [L]                | 10 L                    |
| Protection of the tank              | Glass ceramic           |
| Rated voltage [V/Hz]                | 230V/50Hz               |
| Rated power [W]                     | 1500 W                  |
| Rated pressure of the water tank    | 0.8 MPa                 |
| Insulation [mm]                     | 19 mm                   |
| Heating time from 15°C to 65°C      | 23 min                  |
| Switch On / Off                     | Yes                     |
| Adjustable thermostat               | Yes                     |
| Magnesium anode                     | Yes                     |
| Anode tester                        | No                      |
| Safety valve                        | Yes                     |
| Dimensions H / W / D [m]            | 0.410 x 0.370 x 0.250 m |
| Net weight [kg]                     | 6.50 kg                 |
| Installation                        | sub chiuveta            |
| Warranty (full)                     | 2 years                 |



| Caracteristici tehnice GCU 1515 SRC |                         |
|-------------------------------------|-------------------------|
| Nominal capacity [L]                | 15 L                    |
| Protection of the tank              | Glass ceramic           |
| Rated voltage [V/Hz]                | 230V/50Hz               |
| Rated power [W]                     | 1500 W                  |
| Rated pressure of the water tank    | 0.8 MPa                 |
| Insulation [mm]                     | 19 mm                   |
| Heating time from 15°C to 65°C      | 35 min                  |
| Switch On / Off                     | Yes                     |
| Adjustable thermostat               | Yes                     |
| Magnesium anode                     | Yes                     |
| Anode tester                        | No                      |
| Safety valve                        | Yes                     |
| Dimensions H / W / D [m]            | 0.410 x 0.370 x 0.310 m |
| Net weight [kg]                     | 8.50 kg                 |
| Installation                        | sub chiuveta            |
| Warranty (full)                     | 2 years                 |