

IMIT
TLSC-TLSC/A DUBLU-TERMOSTAT REGLABIL IN IMERSIE



Dublu –termostat in imersie, unipolar, prevazut cu o sonda de dilatare, temperatura se modifica si se limiteaza manual (TLSC) sau automat (TLSC/A) avand o carcasa de protectie din plastic.
Sistem de siguranta suplimentar in caz de rupere a capilarului, completat cu o carcasa de protectie etansa.

DIMENSIUNI

TLSC-TLSC/A	DATE TEHNICE	
	Putere electrica	10 (2,5) A/250 V~ 7 A/400 V~
	Contacte de inrerupere in cazul cresterii temperaturii sau de comutare	
	Temperatura maxima	80 °C
	Temperatura maxima a bulbului	125 °C
	Numarul de cicluri automate	II (100.000)
	Viteza de variatie a temperaturii	1 °K/15 min
	Gradul de protectie	IP 40
	Rezistenta la curenti	PTI 250 (KB 250)
	Presetupa	M 20 X 1,5
	Culoarea carcasei	Oranj**

** Culori disponibile la cerere .

TIPURI STANDARD	
Cod	542714
Model	TLSC
Plaja de reglare	0°/90 °C
Diferenta de temperatura	$\Delta t = 4 \pm 1$ K
Temperatura limita de reglare	90°/110 °C + 0/-6 K
Rearmare manuala	
Carcasa de protectie 1 / 2 " NPT	Ø15X16X100 mm
Cod	542731
Model	TLSC
Plaja de reglare	0°/90 °C
Diferenta de temperatura	$\Delta t = 4 \pm 1$ K
Temperatura limita fixata	100 °C + 0/-6 K
Rearmare manuala	
Carcasa de protectie 1 / 2 " NPT	Ø15X16X100 mm
Cod	542710
Model	TLSC
Plaja de reglare	0°/90 °C

IMIT

Diferenta de temperatura	$\Delta t = 4 \pm 1 \text{ K}$
Temperatura limita de reglare	$90^\circ/110^\circ \text{C} + 0/-6 \text{ K}$
Rearmare manuala	
Carcasa de protectie 1 / 2 " NPT	$\varnothing 15 \times 16 \times 120 \text{ mm}$
Cod	542833
Model	TLSC/A
Temperatura reglabila din exterior	$0^\circ/90^\circ \text{C}$
Temperatura reglabila din interior	$0^\circ/90^\circ \text{C}$
Diferenta de temperatura	$\Delta t = 4 \pm 1 \text{ K}$
Rearmare automata	
Carcasa de protectie 1 / 2 " NPT	$\varnothing 15 \times 16 \times 100 \text{ mm}$
Cod	542720
Model	TLSC/A
Plaja de reglare	$0^\circ/90^\circ \text{C}$
Diferenta de temperatura	$\Delta t = 4 \pm 1 \text{ K}$
Temperatura limita de reglare	$90^\circ/110^\circ \text{C} + 0/-6 \text{ K}$
Rearmare automata	
Carcasa de protectie 1 / 2 " NPT	$\varnothing 15 \times 16 \times 100 \text{ mm}$

Versiuni speciale la cerere

CALOR SRL

Strada Progresul 30-40, Sector 5 – Bucuresti

Tel : 021-411.44.44

Fax : 021-411.36.14

www.calor.ro www.calorserv.ro – ofertare@calor.ro

